



The MSDS format adheres to the standards and regulatory requirements of the United States and may not meet regulatory requirements in other countries.

DuPont
Material Safety Data Sheet

Page 1

L0000055 Pyralux(R) FR Products
Revised 19-FEB-2010

CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Material Identification

PYRALUX is a registered trademark of DuPont.

Product Use

In keeping with DuPont's continuing commitment to safety and the environment, we are providing this MSDS as a service to our customers. This product is classified as non-hazardous under OSHA's Hazard Communication Standard (29 CFR 1910.1200). Pyralux(R) products do create off-gases in normal use. These off-gases are regulated, but are present at such low levels during normal use that no hazardous exposure is anticipated.

Tradenames and Synonyms

Pyralux (R) FR Sheet Adhesive
Pyralux (R) FR Bond Ply
Pyralux (R) FR Coverlay
Pyralux (R) FR Clads

Tradenames and Synonyms (Remarks)

Pyralux (R) FR is the product name of a family of products consisting of flexible Copper Clad Laminates, Coverlay, Bond Ply, and Sheet Adhesive.

The Clads are made of copper foil laminated to polyimide film with an adhesive. The Coverlay and Bond Ply are made of polyimide film with an adhesive, and the Sheet Adhesive is just adhesive.

Company Identification

MANUFACTURER/DISTRIBUTOR

DuPont
1007 Market Street
Wilmington, DE 19898

PHONE NUMBERS

Product Information : 1-800-441-7515 (outside the U.S.
302-774-1000)
Transport Emergency : CHEMTREC 1-800-424-9300(outside U.S.
703-527-3887)
Medical Emergency : 1-800-441-3637 (outside the U.S.
302-774-1000)

COMPOSITION/INFORMATION ON INGREDIENTS

Components

Material	CAS Number	%
Adhesive FR Type		7-71
*Antimony Trioxide	1309-64-4	1-10
Ethylenebistetrabromophthalimide	32588-76-4	2-19
Kapton HN Film		0-90
*Copper Foil	7440-50-8	0-90

Exposure limits for the following may apply:

Benzophenone	119-61-9
*Phenol	108-95-2
*Methanol	67-56-1
2-2'-Diethyl-1,1'biphenyl	13049-35-9
2,6-Dichlorobenzamide	2008-58-4

* Disclosure as a toxic chemical is required under Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Components (Remarks)

The quantity of vapors is estimated to be 1-5 lbs per 100,000 sqft of adhesive.

Vapor evolution results are based on the percentage of weight loss measured by Thermal Gravimetric Analysis (TGA). This weight loss includes water vapor. The pounds of vapor are not all "VOC's" as "defined" by the EPA for Clean Air Act purpose.

HAZARDS IDENTIFICATION

Potential Health Effects

As a part of the hazard assessment process, DuPont has conducted industrial hygiene studies to monitor the potential exposure to the off-gases from this product during normal use. Conclusions from the results of these studies indicate that exposure levels during press lamination using adequate ventilation were well below regulated limits (e.g. an order of magnitude below the exposure limit.) Tests run for antimony trioxide and nuisance dust levels at a drilling/routing station with vacuum exhaust also indicated exposure levels well below regulated limits.

As a result of this test data, DuPont believes the potential exposure to the vapors and dusts of this product to be minimal.

Equipment used for lamination and curing must be adequately exhausted. Consult the DuPont publication "Pyrallux Safe

(HAZARDS IDENTIFICATION - Continued)

Handling". Additional information provided in "Handling & Safety Considerations for the Pyralux PC Curing Process" may also be helpful.

POTENTIAL HUMAN HEALTH EFFECTS OF OVEREXPOSURE:

Inhalation may cause irritation of the upper respiratory passages, with sneezing, coughing and discomfort; or temporary lung irritation effects with cough, discomfort, difficulty breathing, or shortness of breath.

Inhalation, ingestion or skin contact may cause temporary mild depression of the central nervous system with dizziness, confusion, incoordination or drowsiness followed by an asymptomatic period usually ranging from 12 to 24 hours.

Skin contact may cause redness of the skin and dermatitis with itching or rash. Evidence from animal testing on some vapor components suggests that skin permeation can occur in amounts capable of producing the effects of systemic toxicity.

Eye contact with high concentrations of vapors may cause eye irritation with discomfort, tearing or blurring of vision.

Individuals with pre-existing diseases of the central nervous system, liver or kidneys may have increased susceptibility to the toxicity of excessive exposures.

Carcinogenicity Information

The following components are listed by IARC, NTP, OSHA or ACGIH as carcinogens.

Material	IARC	NTP	OSHA	ACGIH
Antimony Trioxide	2B			

FIRST AID MEASURES

First Aid

INHALATION

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

SKIN CONTACT

Flush skin with water after contact. Wash contaminated clothing before reuse.

(FIRST AID MEASURES - Continued)

EYE CONTACT

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

INGESTION

Ingestion is not considered a potential route of exposure.

FIRE FIGHTING MEASURES

Flammable Properties

Flammable limits in Air, % by Volume
LEL : not determined
UEL : not determined

Extinguishing Media

Use media appropriate for surrounding material.

Fire Fighting Instructions

Evacuate personnel to a safe area. Keep personnel removed and upwind of fire. Wear self-contained breathing apparatus. Runoff from fire control may be a pollution hazard.

ACCIDENTAL RELEASE MEASURES

Safeguards (Personnel)

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

HANDLING AND STORAGE

Handling (Personnel)

Do not breathe vapor or mist. Do not breathe dust. Do not get in eyes. Do not store or consume food, drink or tobacco in areas where they may become contaminated with this material.

Thin copper-clad laminates can have sharp metal edges. Personnel handling these materials should be cautioned and proved with suitable protective gloves to prevent cuts.

Good industrial hygiene procedures include washing hands after handling.

(HANDLING AND STORAGE - Continued)

Storage

Do not store or consume food, drink or tobacco in areas where they may become contaminated with this material.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls

Use only with adequate ventilation.

Personal Protective Equipment

Eye/Face : Safety Glasses.
Respirator : USE ADEQUATE VENTILATION WHEN CUTTING OR HEATING.

Exposure Guidelines

Applicable Exposure Limits

Antimony Trioxide

PEL (OSHA) : 0.5 mg/m³, as Sb, 8 Hr. TWA
TLV (ACGIH) : 0.5 mg/m³, handling and use as Sb
Antimony Trioxide Production, A2
8 Hr TWA
AEL * (DuPont) : 0.2 mg/m³, 8 Hr. TWA, as Sb
0.1 mg/m³, 12 Hr. TWA, as Sb

Copper Foil

PEL (OSHA) : 0.1 mg/m³, fume, as Cu, 8 Hr. TWA
1 mg/m³, mist, as Cu, 8 Hr. TWA
TLV (ACGIH) : 0.2 mg/m³, fume, 8 Hr. TWA
1 mg/m³, dusts and mists, as Cu, 8 Hr.
TWA
AEL * (DuPont) : None Established

Benzophenone

PEL (OSHA) : None Established
TLV (ACGIH) : None Established
AEL * (DuPont) : None Established
WEEL (AIHA) : 0.5 mg/m³, 8 Hr. TWA

Phenol

PEL (OSHA) : 5 ppm, 19 mg/m³, 8 Hr. TWA, Skin
TLV (ACGIH) : 5 ppm, 19 mg/m³, 8 Hr. TWA, Skin, A4
AEL * (DuPont) : None Established

Methanol

ECOLOGICAL INFORMATION

Ecotoxicological Information

Aquatic toxicity
Insoluble

DISPOSAL CONSIDERATIONS

Waste Disposal

Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations. Do not burn.

TRANSPORTATION INFORMATION

Shipping Information

DOT/IMO/IATA
Not Regulated.

REGULATORY INFORMATION

U.S. Federal Regulations

TSCA Inventory Status : In compliance with TSCA Inventory requirements for commercial purposes.

State Regulations (U.S.)

WARNING - SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM- Antimony Trioxide; Acrylonitrile <0.01%

OTHER INFORMATION

Additional Information

MEDICAL USE: CAUTION: Do not use in medical applications involving permanent implantation in the human body. For other medical applications see DuPont CAUTION Bulletin No. H-50102.

(Continued)

PRECAUTIONARY STATEMENTS FOR VAPOR CONDENSATE AND
VACUUM PUMP OIL:

WARNING! CAUSES EYE, SKIN AND RESPIRATORY IRRITATION.

Oil in vacuum pump will collect and concentrate less volatile components. Condensate will contain higher percentages of less volatile components. The less volatile components may include acrylate monomers which may cause delayed skin burns and may cause skin sensitization. Avoid contact with eyes, skin and clothing. Avoid breathing mist or vapor. Wash thoroughly with soap and water after handling. Laminators and curing equipment used to process PYRALUX(R) films should be designed with adequate ventilation to exhaust these vapors from the workplace. Vapors may condense on cold surfaces in exhaust ducts. Check these surfaces for condensate build-up before handling.

INFORMATION ON THE CLEAN AIR ACT OF 1990 TITLE VI,
SECTION 611: CONCERNING OZONE DEPLETING SUBSTANCES -

DuPont Riston (R), Vacrel (R), VALU (TM), and Pyralux (R) photopolymer resists and sold masks do NOT contain and are NOT manufactured with either Class I or Class II Ozone Depleting Substances.

For further information regarding the safe use of this material, please refer to DuPont Pyralux(R) FR literature.

The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

Responsibility for MSDS : DuPont Flexible Circuit Materials
MSDS Coordinator
Telephone : (757) 686-8663 OR (919) 248-5027

Indicates updated section.

This information is based upon technical information believed to be reliable. It is subject to revision as additional knowledge and experience is gained.

End of MSDS