

Viton® fluoroelastomer

Version 2.1

Revision Date 12/12/2008

Ref. 150000002397

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name	:	Viton® fluoroelastomer
Product Grade/Type	:	VTR-9088
MSDS Number	:	150000002397
Product Use	:	Rubber products
Manufacturer	:	DuPont Performance Elastomers L.L.C Bellevue Park Corporate Center, 300 Bellevue Parkway Wilmington, Delaware 19809
Product Information	:	1-800-441-7515 (outside the U.S. 1-302-774-1000)
Medical Emergency	:	1-800-441-3637 (outside the U.S. 1-302-774-1139)
Transport Emergency	:	CHEMTREC: 1-800-424-9300 (outside the U.S. 703-527-3887)

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

May cause skin and eye irritation in susceptible persons.

Potential Health Effects

Skin

4,4'-[2,2,2-Trifluoro-1-(trifluoromethyl)ethylidene]diphenol : Causes skin irritation.

Eyes

Benzyltriphenylphosphonium chloride : May cause eye irritation.

Barium sulfate : May irritate eyes. Dust may cause: mechanical irritation with tearing, pain or visual impairment.

bis(4-Chlorophenyl) sulphone : May irritate eyes.

Inhalation

1-Propene, 1,1,2,3,3,3-hexafluoro-, polymer with 1,1-difluoroethene and tetrafluoroethene : Inhalation of decomposition products from overheating may cause lung irritation or shortness of breath. Fluid in the lungs (pulmonary oedema) with cough, wheezing, abnormal lung sounds, possibly progressing to severe shortness of breath and bluish discoloration of the skin (symptoms might be delayed)

Benzyltriphenylphosphonium chloride : Respiratory irritation Breathing difficulties

Viton® fluoroelastomer

Version 2.1

Revision Date 12/12/2008

Ref. 150000002397

Repeated exposure
 Barium sulfate : lung effects

bis(4-Chlorophenyl)
 sulphone : Liver effects Kidney effects

Target Organs
 Barium sulfate : Lungs

bis(4-Chlorophenyl)
 sulphone : Liver Kidney

Carcinogenicity
 None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, or OSHA, as a carcinogen.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Concentration
1-Propene, 1,1,2,3,3,3-hexafluoro-, polymer with 1,1-difluoroethene and tetrafluoroethene	25190-89-0	>95%
4,4'-[2,2,2-Trifluoro-1-(trifluoromethyl)ethylidene]diphenol	1478-61-1	<2 %
Benzyltriphenylphosphonium chloride	1100-88-5	<1 %
Barium sulfate	7727-43-7	<1 %
bis(4-Chlorophenyl) sulphone	80-07-9	<1 %

SECTION 4. FIRST AID MEASURES

Skin contact : Wash off with soap and water. Cool skin rapidly with cold water after contact with hot polymer. Do not peel polymer from the skin. Consult a physician if necessary.

Eye contact : Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. Consult a physician.

Ingestion : If victim is conscious: Drink water as a precaution. Consult a physician.

General advice : When symptoms persist or in all cases of doubt seek medical advice.

Viton[®] fluoroelastomer

Version 2.1

Revision Date 12/12/2008

Ref. 150000002397

SECTION 5. FIRE-FIGHTING MEASURES

Flammable Properties

Flash point : > 204 °C (> 399 °F) open cup

Fire and Explosion Hazard : Burning produces obnoxious and toxic fumes.

Suitable extinguishing media : Carbon dioxide (CO₂), Foam, Water, Dry chemicalFirefighting Instructions : Wear self-contained breathing apparatus and protective suit. Wear neoprene gloves during cleaning up work after a VITON[®] fire. Evacuate personnel to safe areas. Do not allow run-off from fire fighting to enter drains or water courses. The solid polymer can only be burned with difficulty.**SECTION 6. ACCIDENTAL RELEASE MEASURES**

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Safeguards (Personnel) : Ventilate the area. Refer to protective measures listed in sections 7 and 8.

Spill Cleanup : Shovel into suitable container for disposal. Clean contaminated floors and objects thoroughly while observing environmental regulations.

Accidental Release Measures : Try to prevent the material from entering drains or water courses.

SECTION 7. HANDLING AND STORAGE

Handling (Personnel) : Protect from contamination. Provide appropriate exhaust ventilation at dryers, machinery and at places where dust or volatiles can be generated. In case of insufficient ventilation, wear suitable respiratory equipment. Do not breathe dust. Do not breathe fumes evolved from hot polymer. General precaution for all plastics and elastomers: Wash hands before breaks and immediately after handling the product. Regular cleaning of equipment, work area and clothing. When using do not eat, drink or smoke.

Handling (Physical Aspects) : General precaution for all plastics and elastomers: Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Avoid dust formation.

Storage : Keep in a dry, cool and well-ventilated place. Keep containers dry and tightly closed to avoid moisture absorption and contamination.

Viton® fluoroelastomer

Version 2.1

Revision Date 12/12/2008

Ref. 150000002397

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Engineering controls : Use only in area provided with appropriate exhaust ventilation.
- Personal protective equipment
 - Respiratory protection : Where there is potential for airborne exposures in excess of applicable limits, wear NIOSH approved respiratory protection.
 - Hand protection :
 - Eye protection : Safety glasses with side-shields
 - Skin and body protection : If there is a potential for contact with hot/molten material wear heat resistant clothing and footwear.
If VITON® is used above 315°C the surface may contain hydrogen fluoride condensate which may cause severe burns. In this case wear neoprene gloves.
Skin should be washed after contact.

Exposure Guidelines

Exposure Limit Values

Hydrogen fluoride, anhydrous

PEL	(OSHA)	6 ppm	STEL as F
PEL	(OSHA)	3 ppm	TWA
			Skin designation
TLV	(ACGIH)	2 ppm	Ceiling as F
TLV	(ACGIH)	0.5 ppm	TWA as F

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form : sheets, pellets
- Color : white, off-white
- Odor : none
- Density : 1.75 - 1.90 g/cm³
- Water solubility : insoluble

SECTION 10. STABILITY AND REACTIVITY

- Conditions to avoid : Processing temperature > 200 °C (> 392 °F)
Avoid heating for prolonged periods above the recommended upper processing limit.
- Incompatibility : Powdered metals Finely divided aluminium Alkali metals Alkaline earth metals
- Hazardous decomposition : Hazardous decomposition products Hydrogen fluoride, Carbonyl fluoride,

Viton® fluoroelastomer

Version 2.1

Revision Date 12/12/2008

Ref. 150000002397

products Fluorinated hydrocarbons, Fluorinated olefins

Hazardous reactions : Polymerization will not occur.
 During drying, cleaning and moulding, small amounts of hazardous gases and/or particulate matter may be released.
 These may irritate eyes, nose and throat.

SECTION 11. TOXICOLOGICAL INFORMATION

1-Propene, 1,1,2,3,3,3-hexafluoro-, polymer with 1,1-difluoroethene and tetrafluoroethene

Oral ALD : > 5,000 mg/kg, rat

Skin irritation : Species: rabbit
 non-irritant

4,4'-[2,2,2-Trifluoro-1-(trifluoromethyl)ethylidene]diphenol

Oral ALD : 3,400 mg/kg, rat

Skin irritation : irritant

Repeated dose toxicity : Dermal
 No toxicologically significant effects were found.

Oral - gavage, rat
 Reduced body weight gain, Organ weight changes, Hypoactivity

Mutagenicity : Did not cause genetic damage in cultured bacterial cells., Tests on mammalian cell cultures showed mutagenic effects.

Toxicity to reproduction : Experiments have shown reproductive toxicity effects on laboratory animals.

Benzyltriphenylphosphonium chloride

Oral LD50 : 43 mg/kg, rat
 Evident toxicity
 Liver effects
 Kidney effects
 Gastrointestinal effects
 lung effects

Inhalation 4 h ALC : 0.13 mg/l, rat
 Respiratory irritation
 Difficulty in breathing

Skin irritation : No skin irritation

Viton® fluoroelastomer

Version 2.1

Revision Date 12/12/2008

Ref. 150000002397

Eye irritation : irritant

Repeated dose toxicity : Inhalation
Lung damage, Respiratory tract damage

Barium sulfate

Oral LD50 : > 5,000 mg/kg, rat

Skin irritation : Species: human
non-irritantRepeated dose toxicity : Inhalation, animals (unspecified species)
lung effectsMutagenicity : Evidence suggests this substance does not cause genetic damage in
animals., Information given is based on data obtained from similar
product.

bis(4-Chlorophenyl) sulphone

Oral ALD : > 7,500 mg/kg, rat

Skin irritation : Species: rabbit
non-irritantEye irritation : Species: rabbit
Mild eye irritationRepeated dose toxicity : Oral - feed, rat
Liver effectsOral - feed, rat
Kidney effects

Carcinogenicity : Animal testing did not show any carcinogenic effects.

Mutagenicity : Evidence suggests this substance does not cause genetic damage in
animals.**SECTION 12. ECOLOGICAL INFORMATION**

Aquatic Toxicity

1-Propene, 1,1,2,3,3,3-hexafluoro-, polymer with 1,1-difluoroethene and tetrafluoroethene

: The substance is a polymer and is not expected to produce toxic
effects.

48 h EC50 : Daphnia magna (Water flea) > 232 mg/l

Viton® fluoroelastomer

Version 2.1

Revision Date 12/12/2008

Ref. 15000002397

4,4'-[2,2,2-Trifluoro-1-(trifluoromethyl)ethylidene]diphenol	
96 h LC50	: Oncorhynchus mykiss (rainbow trout) < 1 mg/l
72 h ErC50	: Algae > 0.808 mg/l
72 h EbC50	: Algae 0.156 mg/l
48 h EC50	: Daphnia 3.2 mg/l

Additional ecological information : We have no quantitative data concerning the ecological effects of this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste Disposal	: If recycling is not practicable, dispose of in compliance with local regulations. Can be landfilled or incinerated, when in compliance with local regulations. Incinerate only in incinerators capable of scrubbing out acidic combustion products.
Environmental Hazards	: Offer rinsed packaging material to local recycling facilities. If recycling is not practicable, dispose of in compliance with local regulations.

SECTION 14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

SECTION 15. REGULATORY INFORMATION

EINECS Status	: On the inventory, or in compliance with the inventory
TSCA Status	: In compliance with TSCA Inventory requirements for commercial purposes.
AICS Status	: On the inventory, or in compliance with the inventory
DSL Status	: On the inventory, or in compliance with the inventory
ENCS (JP) Status	: On the inventory, or in compliance with the inventory
KECI (KR) Status	: On the inventory, or in compliance with the inventory
PICCS (PH) Status	: On the inventory, or in compliance with the inventory
INV (CN) Status	: On the inventory, or in compliance with the inventory
SARA 313 Regulated Chemical(s)	: SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
California Prop. 65	: Chemicals known to State of California to cause cancer, birth defects or any other harm: none known

Viton[®] fluoroelastomer

Version 2.1

Revision Date 12/12/2008

Ref. 150000002397

PA Right to Know Regulated Chemical(s) : Substances on the Pennsylvania Hazardous Substances List present at a concentration of 1% or more (0.01% for Special Hazardous Substances): No components present on the PA state hazardous substance lists.

NJ Right to Know Regulated Chemical(s) : Substances on the New Jersey Workplace Hazardous Substance List present at a concentration of 1% or more (0.1% for substances identified as carcinogens, mutagens or teratogens): No components present on the NJ state hazardous substance lists.

SECTION 16. OTHER INFORMATION

Restrictions for use : Do not use in medical applications involving permanent implantation in the human body. For other medical applications see DuPont Performance Elastomer's caution bulletin No. H-69237.

Before use read DuPont Performance Elastomer's safety information.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Significant change from previous version is denoted with a double bar.